Rev Date **Properties** 

1/4" Inverted Flare 7/16"-24 UNS-2A

1/4" SAE 45 Degree 7/16"-20 UNF-2A

3/8" SAE 45 Degree 5/8"-18 UNF-2A 1/2" SAE 45 Degree 3/4"-16 UNF-2A 3/4" SAE 45 Degree 1 1/16"-14 UNS




1/8"-27 NPT MBS#402213




1/4"-18 NPT MBS#402024



3/8"-18 NPT MBS#402003



1/2"-14 NPT MBS#402022



3/4"-14 NPT MBS#402133

1/4" Male QD Plug Low Pressure Model 250













MBS#401132






MBS#401207



MBS#401506



MBS#401606



Angles +/- 1 Deg Concentricity +/-.010 Break Sharp Edges .005 R/Chamfer All Dimensions Are In Inches 
 Quality Assurance Provisions Sampling Plan ANSI Z1.4

 Attribute
 +/-.005
 >(+/-.005)
 <(+/-.005)</th>
 Go Ring
 No GO Ring
 Surface

 AQL
 1.0,S-2
 2.5,S-2
 .65,1
 2.5,S-4
 6.5,S-4
 2.5,S-4

See Individual Part Drawings Material: Drawn By: DAG Date: 04-28-2009 Checked By: Date:

Title: M. B. Sturgis Common Thread and Fitting Guide Scale: 1:1 Part Number: 600070 Rev: A00